



FUTURIS

FT001317 - AB Switch Unit

There are 6 independent Layer 3 ethernet switches (SW1, SW2, SW3, SW4, SW5, SW6) in the AB Switch Unit. Ethernet messages on all ports are in UDP protocol.


AB Switch Unit can be connected to 6 internal ethernet switches and 10GBASE-T ethernet port (#7) in the unit and have 1 internal Ethernet Stream Multiplexer (ESM).

I/O Connections

- Ethernet – 15x 1000Base-T
- Ethernet – 1x 10GBASE-T
- DEBUG Ethernet – 1x 10/100
- Serial – 1x RS422, 1x RS485
- 1x Debug UART
- 1X MIL-STD-1553B
- 1X ARINC429

Additional Connections

- JTAG
- Micro SD



Enclosure

- Power – DC 28±5 Volt MIL-STD-1275E
- Power Consumption <30W
- Dimensions – 200 x 170 x 130 mm

Architecture

- Application Processing Unit – 64-bit Cortex-A53
- Real-Time Processing Unit – 32-bit Cortex-R5
- Graphic Processing Unit – ARM Mali™-400 MP2
- Embedded/External Memory – 256KB On-Chip RAM, DDR4-2400 (64-bit) on PS-Side, DDR4 2400 (16bit) on PL-Side, QSPI, eMMC
- Video Codec Unit (VCU) – H.264/H.265

